

# DP4K-32B

Ultra-bright Enhanced 4K DLP Cinema projector for screens up to 32m (105ft)



The Barco DP4K-32B is an ultra-bright Enhanced 4K cinema projector for screens up to 32m (105ft). Featuring Texas Instruments' **1.38" DLP Cinema® chip**, the DP4K-32B is specifically designed to ensure a razor-sharp movie experience on premium cinema screens. It combines this ultra-sharp image quality with an easy-to-use **modular** design, exceptional long lifetime and lowest cost of ownership.

## Vibrant color accuracy

The top-of-the-line DP4K-32B brings stunning images in **Enhanced 4K resolution (4,096 x 2,160)**, combined with ultimate brightness and vibrant color-accuracy time after time.

## Ultimate brightness

Thanks to its highly efficient optical design and patented **DMD cooling system**, the DP4K-32B is the brightest cinema projector in its class - your guarantee for an unequalled, premium cinema experience.

## Also available as fully integrated DC package

The DP4K-32B projector is also available as fully integrated, ready-to-use projection and media server solution. This **DP4K-32Bx package** combines the Barco DP4K-32B projector with a Doremi ShowVault and IMB media server. The package offers a worry-free solution for all theaters that wish to go digital with a minimal hassle and risk. Another major plus is that this integrated system is compatible today with higher frame rates up to 120 fps in 2D and 60 fps in 3D, which makes it a perfect match for playing out HFR releases.



SOUND ASSOCIATES  
PROJECTION | SOUND | CINEMA | DIGITAL

BARCO

Visibly yours

## Technical specifications

## DP4K-32B

<b>Digital MicroMirror Device™</b>	3 x 1.38" DC4K dark metal devices
<b>Native resolution</b>	4,096 x 2,160 pixels
<b>Housing</b>	Hermetically sealed DMDs and optical assembly
<b>Lamp</b>	3kW - 7kW (Xenon lamp)
<b>Light output</b>	33,000 lumens (6.5 kW lamp)
<b>Screen size</b>	Up to 32m / 105 ft wide
<b>Contrast ratio</b>	2,000:1 (typical value when using a high contrast lens)
<b>Digital Video Inputs</b>	Slot for 2 x SMPTE 292M inputs or 4K Integrated Media Block 2 x DVI input both selectable as single and dual link
<b>Control I/O</b>	Ethernet, 8x GPIO, Serial RS232
<b>Prime lenses</b>	1.13 - 1.66 1.27 - 1.86 1.45 - 2.13 1.63 - 2.53 1.95 - 3.26 2.53 - 4.98 equivalent throw ratios for 4K 1.38" DMD
<b>Projector diagnostics</b>	via PC touch panel via Communicator control software via SNMP agent
<b>Power requirements</b>	3W+N+PE 230/400V 16A 50-60Hz or 3W+PE 208V 27A 50-60Hz 30,000 BTU/hr (with 6.5kW - 7kW lamp)
<b>Dimensions</b>	604(H) x 754(W) x 1129(D) mm 23.78(H) x 29.69(W) x 44.45(D) inch NB.: min. 5 cm of air inlet spacing required at the bottom of projector
<b>Weight</b>	141 kg (311 lbs)
<b>Ambient temperature</b>	35°C / 95°F Max.
<b>Exhaust airflow</b>	350 CFM
<b>Standard Features</b>	CLO (Constant Light Output) Powerful SNMP agent Motorized/memorized lens (focus, zoom & shift) HDCP support Full 2K triple flash 3D Advanced patented DMD cooling
<b>Options</b>	4K Integrated Media Block ACS-2048 3D add-ons Touch panel Pedestal

