

NEC NC603L

Digital Cinema Projector

Preliminary Datasheet





Benefits

Compact, lightweight and quiet – easy installation in small projection booths, easy transportation for mobile cinemas and perfectly suited for boothless cinemas.

Sealed optical engine – minimising dust ingress, consistent performance is assured and no special maintenance is required.

Highly flexible – with no exhaust system required, the NC603L is suitable for floor and ceiling installation and versatile content playback.

Virtually zero maintenance – no lamp and no filter replacement costs, no maintenance personnel costs and no lamp stock due to the innovative Laser Light engine.

Enjoy a Lower TCO – highest reliability, maintenance-free operation, low power consumption and up to 50000 hours life; the Laser light source results in a significantly lower total cost of ownership.

Product Information

| Product Name | NEC NC603L |
|---------------|--------------------------|
| Product Group | Digital Cinema Projector |
| Order Code | 60005938 |

Optical

| - | |
|--------------------|---|
| Projection Method | 3-chip DLP Cinema® Technology |
| Screen Size [m] | up to 11 in DCI colour (1.8 Gain screen) |
| Brightness | 6000 Lumen |
| Contrast Ratio | 1650:1 |
| Light Source | Laser Light Source, expected life: up to 50000 h ¹ |
| Lens | Zoom / Focus / Shift: Motorized |
| | Other: Range of shift is dependent on lens |
| | Primary Lenses: NP-9LS12ZM1: 1.2-1.72:1; NP-9LS13ZM1: 1.33-2.1:1; NP- |
| | 9LS16ZM1: 1.62-2.7:1; NP-9LS20ZM1: 2.09-3.9:1 |
| DMD Specifications | 2048 x 1080 |
| | Chip: 0.69" S2K, DLP Cinema® Technology |
| Cooling Method | Liquid: Air and liquid cooling inside |
| | |

Connectivity Projector

| External Controls | 1 x GPIO (3D) (D-sub 15 pin female); 1 x GPIO (D-sub 37 pin female); 1 x RJ45 |
|-------------------|---|
| | 100Base-T |

Environmental Conditions

| Operating Temperature [°C] | 10 to 35 |
|----------------------------|---------------------------|
| Operating Humidity [%] | 10 to 85 - non-condensing |
| Storage Temperature [°C] | -10 to 50 |
| Storage Humidity [%] | 10 to 85 - non-condensing |

Electrical

| Power Supply | Built-in power supply |
|------------------------|--|
| | Projector Power Supply Unit: 200 to 240V AC, 50/60Hz, single phase |
| Rated Input Current | Projector power: 7.4A @ 200V-240V |
| Power Consumption [W] | 890 max. |
| Heat Dissipation (BTU) | 3037 max. |

Mechanical

| External Dimensions (W x | 680 x 333 x 860 (without lens and protrusions) |
|--------------------------|--|
| H x D) [mm] | |
| Weight [kg] | 59 (without lens) |

| Fan Noise [dB (A)] | < 39 |
|---------------------------|--|
| Additional Features | |
| Special Characteristics | Built-in IMS (IMS3000, optional); Compact model; Dust sealed optical engine; Full HFR 3D support; Laser Light System; Latest digital technology; Low TCO; Metal filter |
| Green Features | |
| Ecological Materials | Laser technology reduces power usage and reduces replacement materials required |
| Interfaces: Dolby IMS300 | 00 (optional) |
| External Controls | 2 x RJ45 (4 GPI and 6 GPO); 2 x RJ45 Gigabit Ethernet |
| Input Terminals | 1 x USB Type 2.0; 2 x 3GSDI bidirectional (input and output); 2 x USB Type 3.0; eSATA; HDMI |
| Output Terminals | 2 x RJ45 (16-channel AES3-EBU Digital Audio) |
| Additional Features | HFR 3D Support (48 Hz/eye, 60 Hz/eye); Integrated SMS; Integrated Storage: 2 TB (DCP, RAID5); NAS support |
| Manufacturer | Dolby (The Dolby IMS3000 is not a NEC product. NEC shall not in any way be liable for any product specifications). |
| Regulations | |
| Europe | EN55035; EN61000-3-2/-3-3 (Marking: TUV, CE); EN62368-1/EN55032 Class A |
| Laser / Lamp standard | EN60825-1 Ed3:2014 Class1; EN62471-5 Ed1:2015 Risk Group3; IEC60825-1 Ed3:2014 Class1; IEC62471-5 Ed1:2015 Risk Group3 |
| Morocco | NM EN55024; NM EN60950-1; NM EN61000-3-2/-3-3 (Marking Morocco mark) |
| Other EMEA | EN55024; EN55032 Class A; EN55035; EN60950-1; EN61000-3-2/-3-3 (Marking CE) |
| Russia/Belarus/Kazakhstan | CISPR24; IEC61000-3-2/-3-3 (Marking: EAC) |
| United Arab Emitates | ECAS:IEC60950-1 (Marking: ECAS) |
| Warranty | |
| Warranty | 2 years, parts warranty |
| Light Source | 2 years or 7500h (whatever comes first) |

¹ 50% of initial brightness at the end of specified laser life time at 25 degree ambient temperature, under normal usage condition, not covered by standard warranty

This document is © 2023 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 23.08.2023