

DP2K-10Sx

Small integrated DLP Cinema® projector for screens up to 10m (33ft) wide



Specifically designed for smaller screens

The Barco DP2K-10Sx projector is a compact and fully integrated digital cinema projector designed for the special needs of smaller theaters, independent cinemas and art houses.

Digital cinema projector with Integrated Media Server

The DP2K-10Sx projector comes as a fully integrated, DCI-compliant projector – including a 0.69" DLP Cinema® projector, a high-grade cinema lens and an Integrated Media Server with integrated redundant storage. As such, it is the perfect choice for exhibitors looking for a worry-free solution to go digital with a minimal hassle and risk.

Why you'll love Barco's DP2K-10Sx?

- **Exceptional brightness** thanks to its superior optical efficiency, patented sealed engine and DMD cooling system
- **Vibrant and stable colors** due to standard Xenon lamps
- **Crisp images over time** thanks to the acclaimed manual color convergence mechanism of the larger Barco projectors
- **Ultimate peace of mind** and easy regulatory compliance thanks to the 'out-of-the-box' DCI-compliance of the included lamp, lens and storage technology
- **No need for additional hardware investment and zero worries** thanks to the Integrated Media Server with integrated redundant storage
- **Full compatibility** with all internal and external 3D systems, including a multitude of alternative content input capabilities
- **Perfect image ratio in every setup** thanks to full range of motorized lenses
- **Easy transport, installation and service** thanks to its integrated handles, user-friendly software tools and smart modular architecture
- **Lowest operating cost** through energy-efficient Xenon lamps, a standby eco-mode, reusable air filters and commonality of components with other Barco projectors

Also available without Integrated Media Server

The DP2K-10Sx integrated digital cinema projector is also available as projector-only solution. The **DP2K-10S** comes with the same features as the DP2K-10Sx but does not include an Integrated Media Server.

BARCO

Visibly yours

Technical specifications

| Preliminary technical specifications. These are subject to change without prior notice. | |
|---|--|
| Digital MicroMirror Device™ | 3 x 0.69" DC2K dark metal devices |
| Native resolution | 2,048 x 1,080 pixels |
| Housing | Hermetically sealed DMDs and optical assembly |
| Lamp | 2.2kW, short-arc Xenon |
| Screen size | Up to 10m/33 ft wide (screen gain 1.2 @ 14ftl) |
| Contrast ratio | 1,850:1 |
| Prime Lenses | Fully motorized 1.2 - 1.7 1.34 - 1.9 1.5 - 2.15 1.7 - 2.55 2.0 - 3.9 |
| Integrated Media Server (IMS-1000) | JPEG2000 2K & 4K DCI play-out High Frame Rates 3D up to 120fps (60fps per eye) JPEG 2000 bit-rates up to 500Mbps Dolby3D color-correction MPEG-2 H.264 2 x 3G-SDI inputs 1x HDMI 1.4a input (BluRay 3D / 4K) 16x AES/EBU audio channels (2x RJ45) 4x GPI, 6x GPO (2x RJ45) 2x ETH for management & ingest 3x front-accessible USB for ingest 1x eSATA port for fast ingest |
| Integrated storage (IMS-1000) | 2 TB effective storage (RAID-5) 3 x hot-swappable 2.5" hard-drives |
| SMS Software (IMS) | Show Player/editor/scheduler Automation, 3D, ingest TMS integration |
| Projector Diagnostics | Via Communicator control software Via Communicator LITE control software (web-based) Via SNMP agent |
| Power Requirements | 220 V |
| Projector dimensions (HxWxD) | 325 x 626 x 925 mm 12.8 x 24.7 x 36.4 inch |
| Projector weight | Recessed handles for easy carrying 56.5 kg / 125 lbs for carrying (lamp-house removed) (66.5 kg / 147 lbs total weight) |
| Ambient temperature | 35°C / 95°F Max. |
| Options | ACS-2048 3D add-ons Touch screen monitor Pedestal Exhaust-free adaptor Frame for easy carrying and installation Auro 11.1 audio decoder license (IMS) Live 3D: RealD LIVE or Sensio® Hi-Fi 3D licenses (IMS) RealD Ghostbusting license (IMS) |