

NEC NC3200S

Order Code: 60002816, 60002996

NEC NC3200S Digital Cinema Projector

Bring your establishment into the future with the NEC NC3200S DLP® Digital Cinema Projector. Delivering exceptional image quality, brightness, resolution, contrast and colours together with a wealth of new revenue generation opportunities and backed by the trusted performance of one of the biggest names in Digital Cinema technology.

An ideal solution for cinemas, theatres, conference halls, auditoriums.

DELIVERING GENUINE BENEFITS

Bring Your Establishment Into The IT Age - easy distribution of movies and media, copyright and licensing management offered in all IT formats.

Enjoy Lower TCO - with easy servicing, more durable components and advanced servicing options. You can enjoy better quality imaging whilst experiencing an overall lower cost of ownership.

Generate Greater Per Seat Revenue - achieve additional income from showing higher quality, more entertaining media and arranging alternative sports, broadcast and education media during off-peak operational times.

Play Captivating 3D Content - take your establishment into the next generation and stay ahead of the competition with the latest digital content, an increasingly essential element of the latest movies and media.



OUTSTANDING PERFORMANCE

- **Suitable for Smaller Venues.** Create outstanding images for screens up to 32 m wide using 7.0KW high-efficiency lamp.
- **High Resolution and Content** utilising DLP® Cinema Technology from Texas Instruments. Exceptional image and colour quality with contrast ratio of 2200:1 or higher by using DMD chips that support a resolution of 2048 x 1080. This projector faithfully reproduces digital cinema and high-definition input sources requiring superior colour reproduction and wide gradation.
- **High Reliability.** Newly designed separate cooling system creates positive air pressure internally to prevent contaminations from entering the optical system and lamp area. Lamp cooling air flow is separate from the main optics and electronics.
- **Auto Lamp Brightness and Control** minimise fluctuations that occur during the life of the lamp. The brightness level will not decrease as the lamp is consumed. These projectors optimise lamp performance and ensure the brightest and most uniform image possible for the life of the lamp.



OUTSTANDING PERFORMANCE

- **Minimal Maintenance** and trouble-free lamp replacement. Technicians can replace lamps simply from the back of the projector even in cramped space.
- **Simple Operation.** One touch operation, ergonomic keyboard layout and memory functions. Optional scaler/switcher for alternative content processing.
- **Built-in Web Server.** Access and control projectors from any authorised web browser.
- **Wide Converter Lens and Motorized Turret**
- **Full Panel 3D triple-flash Capability.** Amazing 3D brightness.

SPECIAL CHARACTERISTICS

Latest digital technology, reduced costs, stunning and varied content, additional security, unsurpassed quality.



Ecological Materials Eliminate waste and landfill implications associated with 35mm media

Technical Specification NEC NC3200S	
OPTICAL	
Projection Method	3-chip DMD reflection method
Screen Size [m]	12 to 32
Brightness	33000 lumens when using 7KW high-efficiency Xenon lamp bulb
Contrast Ratio	2200 : 1 or above (full on / off)
Lamp	High-efficiency Xenon lamp options (7KW)
Lens	Zoom / Focus: Motorized; Motorized Shift: Horizontal/Vertical Motorized Other: Dowser (light shutter); Lens memory stores lens setting (shift/zoom/focus); Range of shift is dependent on lens Primary Lenses: 1.25 to 1.45:1 zoom; 1.44 to 2.05:1 zoom; 1.6 to 2.4:1 zoom; 1.8 to 3:1 zoom; 2.15 to 3.6:1 zoom; 3 to 4.3:1 zoom; 4.3 to 6:1 zoom
DMD Specifications	2048 x 1080 Chip: 1.25" DLP Tilt Angle [°]: 12
Cooling Method	Liquid: Liquid cooling inside, air cooling with dust-preventing electrostatic filter Total thermal dissipation [BTU]: 35500 Projector exhaust [m³/min]: 16 Demand of exhaust duct: Yes
CONNECTIVITY	
External Controls	1 x D-Sub 37 pin (GPIO); 1 x D-Sub 15-pin (3D); 1 x D-Sub 9 pin (RS-232); 1 x D-Sub 9-pin; 1 x Remote control connector; 1 x USB port (TypeA); 1 x RJ45
Input Terminals	4 x HDSDI (BNC); 2 x DVI-D
ELECTRICAL	
Power Supply	Projector Power Supply Unit: 100 to 240V AC, 50/60Hz, single phase Lamp power supply unit [KVA]: 200 to 230V / 380 to 415V AC, 50/60Hz, 3 phases
Power Consumption [W]	9955 max. Projector Power: 455 Lamp Power: 9,500
ENVIRONMENTAL CONDITIONS	
Operating Temperature [°C]	5 to 35
Operating Humidity [%]	10 to 85 - non-condensing
Storage Temperature [°C]	-10 to 50
MECHANICAL	
External Dimensions (W x H x D) [mm]	Projector Head ¹ : 700 x 503 x 1,124 Lamp power supply unit: 594 x 452 x 397
Weight [kg]	99 (without lense); Lamp power supply unit : Approx. 52
Fan Noise [dB (A)]	< 66
Regulations Europe	EN55022 1998, Class A; EN55024 1998; EN61000-3-11; EN61000-3-12
OPTIONAL ACCESSORIES	
Optional Accessories	Air filter; Built-in alternative content processor; Optional input boards for alternative content processor; Wide converter lens and motorized turret
WARRANTY	
Warranty	2 year, parts warranty

¹ Excluding lens, lens hood and exhaust stack